

High Efficiency - Twin Alternating Water Conditioner



9000



9100

9000 * 9100 Twin Econominder

These top quality control valves are available in 24V or 110V. The regeneration cycles are automatic and dependable.

9100 Valve Body

Valve body and meter module are molded from glass-reinforced Noryl for exceptional strength and durability.

9000 Valve Body

Lead free brass valve control.

Proven Reliability

THOUSANDS are in service in western United States.

Stainless Steel

The outer covering is for U.V protection and algae inhibition on outdoor installations (Optional). 8"-12" Tanks**

Poly Glass Tanks

Tanks constructed of a high-density polyethylene inner shell, thermal wound with fiberglass. These tanks are totally non-corrosive!

Dual Pressure Tanks

System permits one tank to always be in service during regeneration cycles.

Limited Lifetime Warranty

On pressure tanks and brine tanks. There is a full 3 year warranty on parts.

Locally Manufactured by Water Tec of Tucson Inc.

From only the highest quality components at our facility in TUCSON, ARIZONA.

Over 40 Year Reputation

Of immaculate customer service satisfaction, integrity and quality!

**MADE IN
THE U.S.A.**

Authorized Distributor:



Providing service after the sale since 1967.



Specifications

| VALVE MODEL | TOTAT CAPACITY IN GRAINS | TOTAL RESIN VOLUME | RESIN TANK SIZE | BRINE TANK SIZE | # SALT USED PER REGEN. CYCLE | MAX FLOW RATE (GPM) |
|-------------|--------------------------|--------------------|-----------------|-----------------|------------------------------|---------------------|
| 9000 | 45000 | 1.5 | 08X40 | 11X11X36 | 6-9 LBS. | 10 |
| 9100 | 45000 | 1.5 | 08X40 | 11X11X36 | 6-9 LBS. | 10 |
| 9000 | 60000 | 2 | 09X48 | 18X30 | 8-12 LBS. | 13 |
| 9100 | 60000 | 2 | 09X48 | 18X30 | 8-12 LBS. | 13 |
| 9000 | 90000 | 3 | 10X54 | 18X40 | 12-18 LBS. | 16 |
| 9100 | 90000 | 3 | 10X54 | 18X40 | 12-18 LBS. | 16 |
| 9000 | 120000 | 4 | 12X52 | 18X40 | 16-24 LBS. | 22 |
| 9100 | 120000 | 4 | 12X52 | 18X40 | 16-24 LBS. | 22 |
| 9000 | 150000 | 5 | 13X54 | 18X40 | 20-36 LBS | 26 |
| 9100 | 150000 | 5 | 13X54 | 18X40 | 20-36 LBS | 26 |
| 9000 | 180000 | 6 | 14X65 | 24X50 | 24-36 LBS | 28 |
| 9100 | 180000 | 6 | 14X65 | 24X50 | 24-36 LBS | 28 |
| 9000 | 240000 | 8 | 16X65 | 24X50 | 32-48 LBS | 28 |
| 9100 | 240000 | 8 | 16X65 | 24X50 | 32-48 LBS | 28 |

**ALL TWIN ALTERNATING SYSTEMS WILL CONSIST OF:
ONE CONTROL VALVE
TWO RESIN TANKS
ONE BRINE TANK**

***** UNITS WILL BE SHIPPED LOADED UNLESS SPECIFIED*****

SYSTEM INCLUDES A 3/4" OR 1" BYPASS VALVE

1 1/4" BYPASS AVAILABLE AT ADDITIONAL COST

OPERATING PRESSURE IS 40 - 90 PSI @ 34F - 110F

