

Backwashing Carbon Filter

WS125

The Clack Water Specialist Control features a solid state microprocessor with easy access settings. The control valve design provides optimum service and backwash flow rates. Designed for use with water filtration system. These systems are fully automatic and self-cleaning. The valve body is molded from glass-reinforced Noryl for exceptional strength and durability.

Limited Lifetime Warranty

On pressure tanks, and a full 5 year warranty on parts (Control valve).

Locally Manufactured by:

Water Tec of Tucson Inc.

From the highest quality components at our facility in TUCSON, ARIZONA.

Over 45 Year Reputation

Of immaculate customer service satisfaction, integrity and quality!



The Clack Water Specialist Control

Tank Jackets

The outer covering is for U.V protection and algae inhibition on outdoor installations (Optional plastic or stainless steel jackets)

Poly Glass Tanks

Tanks constructed of a high-density polyethylene inner shell, thermal wound with fiberglass. These tanks are totally non-corrosive!

**MADE IN
THE U.S.A.**

Authorized Distributor:



Providing service after the sale since 1967.



Specifications

MODEL NUMBER	CF Car- bon	TANK SIZE	WATER WASTE PER BACKWASH	FLOW RATE
FS-AC-WS1-1054	2	10X54	65	3 GPM**
FS-AC-WS1-1252	2	12X52	95	4 GPM**
FS-AC-WS1-1354	3	13X54	115	5 GPM**
FS-AC-WS1-1465	3	14X65	130	6 GPM**
FS-AC-WS1-1665	4	16X65	170	7 GPM**
FS-AC-WS1-1865	5	18X65	215	8 GPM**
FS-AC-WS1-2162	7	21X62	290	10 GPM**

**FLOW RATE IS BASED ON AN EBCT OF 7 MIN

*Depending on local water conditions

**SYSTEM INCLUDES A BYPASS VALVE
AND 1-1/4" X 1-1/2" PIPING BOSSES.**

OPERATING PRESSURE IS 40 - 90 PSI @ 34F - 110F

The pre-brine refill feature is preferred when using Potassium, this feature assures that there is no standing water in the brine tank so there is no issue with Potassium hardening in the brine tank!

