

Automatic Water Conditioner

Fleck 5600 Econominder Control Valve

These top quality control valves are available in 24V or 110V. The regeneration cycles are automatic and dependable. Valve body and meter module are molded from glass-reinforced Noryl for exceptional strength and durability.

Limited Lifetime Warranty

On pressure tanks and brine tanks, and a full 3 year warranty on parts (Control valve & brine tank internals).

Locally Manufactured by:

Water Tec of Tucson Inc.

From the highest quality components at our facility in TUCSON, ARIZONA.

Proven Reliability

THOUSANDS are in service in western United States

Over 45 Year Reputation

Of immaculate customer service satisfaction, integrity and quality!



TWIN-TANK



CABINET

Tank Jackets

The outer covering is for U.V protection and algae inhibition on outdoor installations (Optional plastic or stainless steel jackets)

Poly Glass Tanks

Tanks constructed of a high-density polyethylene inner shell, thermal wound with fiber-glass. These tanks are totally non-corrosive!

Compact Space Saving

The built-in brine tanks cabinet unit for indoor installations. The valve may be installed in various positions for accessibility.

**MADE IN
THE U.S.A.**

Authorized Distributor:

Specifications

MODEL NUMBER	GRAINS CAPACITY	TANK SIZE	BRINE TANK	SALT LBS. USED PER REGEN. CYCLE	WATER GAL. USED PER REGEN. CYCLE	FLOW RATE
RT 1035 56M	32,000	10X35	12X24X42	9 LBS. *	55 GAL. *	8 GPM
TT 948 56M	32,000	09X48	18X33	9 LBS. *	55 GAL. *	8 GPM
TT 1054 56M	48,000	10X54	18X40	12 LBS. *	60 GAL. *	10 GPM

*DEPENDING ON LOCAL
WATER CONDITIONS

SYSTEM INCLUDES A 3/4" OR 1" BYPASS VALVE

1 1/4" BYPASS AVAILABLE AT ADDITIONAL COST

OPERATING PRESSURE IS 40 - 90 PSI @ 34F - 110F

