

Conditioned Water

Controls to fit Your needs!



FLECK Proflo-SE



CLACK WS1



FLECK 7000-SE

In Your Kitchen

- **Dish Sparkler**
Eliminates streaks & spots.
- **Scrubbing Helper**
Eliminates film and soap scum.
- **Skin Softener**
Hard water makes skin dry and Rough.

Around Your Home

- **Hot Water Guard**
Adds life to your hot water heater by eliminating scale buildup.
- **Pipe Protector**
Scale clogs plumbing and reduces water pressure.
- **Faucet Preserver**
Eliminates corrosion and lengthens service life and beauty.

In Your Pocket Book

- **Money Stretcher**
Save money on cleaning supplies and energy
- **Soap Saver**
Use less soap and chemicals.
- **Clothes Saver**
Clothes last longer and stay brighter too.



Water Softeners 1"/ 1.25"/ 1.50"

Solid State Microprocessor Based Controls

Proflo SXT

Product Features

Flow Rates (50psi Inlet) Valve Alone:

- Bright LCD display
 - Displays time of day in hours and minutes
 - Volume of soft water remaining
 - Easy, friendly programming
 - EEPROM memory
 - Capacitor backup
 - Strong, weather-resistant, Noryl[®] valve body
 - 3/4", 1", 1-1/4" Inlet / Outlet
 - Versatile programming to fit application
 - Applications up to 16" dia. tanks
- Continuous (15psi drop) 21GPM
 - Peak (25psi Drop) 27GPM

WS1—WS125

Product Features

Flow Rates (50psi Inlet) Valve Alone:

- Bright LCD display
 - Displays time of day in hours and minutes
 - Volume of soft water remaining
 - Easy, friendly programming
 - EEPROM memory
 - Battery back-up
 - Strong, weather-resistant, Noryl[®] valve body
 - 3/4", 1", 1-1/4" & 1-1/2" Inlet / Outlet
 - Versatile programming to fit application
 - Applications up to 21" dia. tanks
- Continuous (15psi drop) 27GPM
 - Peak (25psi Drop) 40GPM

7000 SXT

Product Features

Flow Rates (50psi Inlet) Valve Alone:

- Bright LCD display
 - Displays time of day in hours and minutes
 - Volume of soft water remaining
 - Easy, friendly programming
 - EEPROM memory
 - Capacitor backup
 - Strong, weather-resistant, Noryl[®] valve body
 - 1-1/4" & 1-1/2" Inlet / Outlet
 - Versatile programming to fit application
 - Applications up to 24" dia. tanks
- Continuous (15psi drop) 27GPM
 - Peak (25psi Drop) 46GPM

Authorized Distributor:

Model: _____

Specifications: _____

Capacity: _____

Dimensions: _____

Notes: _____



Visit our showroom and manufacturing facility and find out why Arizona's homeowners and businesses have trusted their water problems to Water Tec of Tucson for over 45 years!