Point of Entry Filter System

The P.O.E. Water Filter System eliminates unwanted substances from water. Designed for use with a water softening system or as a point of entry water filter, the P.O.E system is fully automatic and self cleaning. High Grade Granular Activated Carbon removes Chloramines, Chlorine and other Volatile Organic Contaminants as well as color taste and odor from water as it flows through the filter bed. Other filter media is available for specific requirements.



The Clack Water Specialist Control features a solid state microprocessor with easy access settings. The control valve design provides optimum service and backwash flow rates. Designed for use with water filtration system. These systems are fully automatic and self-cleaning The valve body is molded from glass-reinforced Noryl for exceptional strength and durability.



Authorized Distributor:









MODEL NUMBER	TANK SIZE	MEDIA CAPACI- TY	GALLONS OF WATER USED PER BACKWASH	FLOW RATE
FS-AC-WS1-0948	09X48	1 CU. FT.	15 GALLONS	8 GPM
FS-AC-WS1-1054	10X54	1.5 CU. FT.	30 GALLONS	10 GPM
FS-AC-WS1-1252	12X52	2 CU. FT	60 GALLONS	12 GPM
FS-AC-WS1-1354	13X54	2.5 CU. FT	80 GALLONS	13 GPM
FS-AC-WS1-1465	14X65	3 CU. FT	110 GALLONS	16 GPM
FS-AC-WS1-1665	16X65	4 CU. FT	210 GALLONS	21 GPM

HIGH GRADE GRANULAR ACTIVADED CARBON

SYSTEM INCLUDES A 3/4" OR 1" BYPASS VALVE

1 1/4" BYPASS AVAILABLE AT ADDITIONAL COST

OPERATING PRESSURE IS 40 - 90 PSI @ 34F - 110F

ADDATIONAL FILTRATION MEDIAS AVAILABLE FOR TREATING SEDIMENT, IRON AND OTHER ISSUES

<u>Maintenance</u> The filtration media should be replaced every two years.

Locally Manufactured by:

Water Tec of Tucson Inc. From the highest quality components at our facility in TUCSON, ARIZONA.

Proven Reliability

THOUSANDS are in service in western United States

Over 40 Year Reputation

Of immaculate customer service satisfaction, integrity and quality!

Tank Jackets

The outer covering is for U.V protection and algae inhibition on outdoor installations. (Optional plastic or stainless steel jackets)

Poly Glass Tanks

Tanks constructed of a high-density polyethylene inner shell, thermal wound with fiberglass. These tanks are totally non-corrosive!